

Document: Omega Glass Clear Canopy, Major Canopy Dimensions
 Description: Omega Glass Clear Canopy, Lean-To style, post-supported,
 Glass Clear Plate Polycarbonate Roof Panels

Page 1 of 4

Key Canopy Dimensions for Roof Pitch 5 degrees

Width (m)	Projection (m)	Actual width (mm)	Actual Projection (mm) to outside edge of eaves beam (roof pitch 5 degrees)	Projection wall to inside face of supporting post (mm) Roof Pitch = 5 degrees	Dimension from bottom of wall plate to bottom of eaves beam (mm) Roof pitch = 5 degrees	Vertical dimension from top of Wall plate to bottom of wall plate (mm)	Vertical dimension of face of wall plate immediately adjacent wall (mm)
2.1	1.5	2106	1578	1500	153	146	124
2.8	1.5	2806	1578	1500	153	146	124
3.5	1.5	3506	1578	1500	153	146	124
4.2	1.5	4206	1578	1500	153	146	124
4.9	1.5	4906	1578	1500	153	146	124
5.6	1.5	5606	1578	1500	153	146	124
6.3	1.5	6306	1578	1500	153	146	124
7.0	1.5	7006	1578	1500	153	146	124
7.7	1.5	7706	1578	1500	153	146	124
8.4	1.5	8406	1578	1500	153	146	124
9.1	1.5	9106	1578	1500	153	146	124
9.8	1.5	9806	1578	1500	153	146	124
10.5	1.5	10506	1578	1500	153	146	124
2.1	2.0	2106	2078	2000	196	146	124
2.8	2.0	2806	2078	2000	196	146	124
3.5	2.0	3506	2078	2000	196	146	124
4.2	2.0	4206	2078	2000	196	146	124
4.9	2.0	4906	2078	2000	196	146	124
5.6	2.0	5606	2078	2000	196	146	124
6.3	2.0	6306	2078	2000	196	146	124
7.0	2.0	7006	2078	2000	196	146	124
7.7	2.0	7706	2078	2000	196	146	124
8.4	2.0	8406	2078	2000	196	146	124
9.1	2.0	9106	2078	2000	196	146	124
9.8	2.0	9806	2078	2000	196	146	124
10.5	2.0	10506	2078	2000	196	146	124
2.1	2.5	2106	2578	2500	241	146	124
2.8	2.5	2806	2578	2500	241	146	124
3.5	2.5	3506	2578	2500	241	146	124
4.2	2.5	4206	2578	2500	241	146	124
4.9	2.5	4906	2578	2500	241	146	124
5.6	2.5	5606	2578	2500	241	146	124
6.3	2.5	6306	2578	2500	241	146	124
7.0	2.5	7006	2578	2500	241	146	124
7.7	2.5	7706	2578	2500	241	146	124
8.4	2.5	8406	2578	2500	241	146	124
9.1	2.5	9106	2578	2500	241	146	124
9.8	2.5	9806	2578	2500	241	146	124
10.5	2.5	10506	2578	2500	241	146	124
2.1	3.0	2106	3078	3000	283	146	124
2.8	3.0	2806	3078	3000	283	146	124
3.5	3.0	3506	3078	3000	283	146	124
4.2	3.0	4206	3078	3000	283	146	124
4.9	3.0	4906	3078	3000	283	146	124
5.6	3.0	5606	3078	3000	283	146	124
6.3	3.0	6306	3078	3000	283	146	124
7.0	3.0	7006	3078	3000	283	146	124
7.7	3.0	7706	3078	3000	283	146	124
8.4	3.0	8406	3078	3000	283	146	124
9.1	3.0	9106	3078	3000	283	146	124
9.8	3.0	9806	3078	3000	283	146	124
10.5	3.0	10506	3078	3000	283	146	124
2.1	3.5	2106	3538	3578	327	146	124
2.8	3.5	2806	3538	3578	327	146	124
3.5	3.5	3506	3538	3578	327	146	124
4.2	3.5	4206	3538	3578	327	146	124
4.9	3.5	4906	3538	3578	327	146	124
5.6	3.5	5606	3538	3578	327	146	124
6.3	3.5	6306	3538	3578	327	146	124
7.0	3.5	7006	3538	3578	327	146	124
7.7	3.5	7706	3538	3578	327	146	124
8.4	3.5	8406	3538	3578	327	146	124
9.1	3.5	9106	3538	3578	327	146	124
9.8	3.5	9806	3538	3578	327	146	124
10.5	3.5	10506	3538	3578	327	146	124
3.1	4.0	3106	4028	4068	370	146	124
4.2	4.0	4206	4028	4068	370	146	124
5.2	4.0	5206	4028	4068	370	146	124
6.3	4.0	6306	4028	4068	370	146	124
7.4	4.0	7406	4028	4068	370	146	124
8.4	4.0	8406	4028	4068	370	146	124
9.0	4.0	9006	4028	4068	370	146	124
9.4	4.0	9406	4028	4068	370	146	124
10.0	4.0	10006	4028	4068	370	146	124

Document: Omega Glass Clear Canopy, Major Canopy Dimensions
 Description: Omega Glass Clear Canopy, Lean-To style, post-supported,
 Glass Clear Plate Polycarbonate Roof Panels

Key Canopy Dimensions for Roof Pitch 10 degrees

Width (m)	Projection (m)	Actual width (mm)	Actual Projection (mm) to outside edge of eaves beam (roof pitch 10 degrees)	Projection wall to inside face of supporting post (mm) Roof Pitch = 10 degrees	Dimension from bottom of wall plate to bottom of eaves beam (mm) Roof pitch = 10 degrees	Vertical dimension from top of Wall plate to bottom of wall plate (mm)	Vertical dimension of face of wall plate immediately adjacent wall (mm)
2.1	1.5	2106	1568	1491	277	146	124
2.8	1.5	2806	1568	1491	277	146	124
3.5	1.5	3506	1568	1491	277	146	124
4.2	1.5	4206	1568	1491	277	146	124
4.9	1.5	4906	1568	1491	277	146	124
5.6	1.5	5606	1568	1491	277	146	124
6.3	1.5	6306	1568	1491	277	146	124
7.0	1.5	7006	1568	1491	277	146	124
7.7	1.5	7706	1568	1491	277	146	124
8.4	1.5	8406	1568	1491	277	146	124
9.1	1.5	9106	1568	1491	277	146	124
9.8	1.5	9806	1568	1491	277	146	124
10.5	1.5	10506	1568	1491	277	146	124
2.1	2.0	2106	2058	1981	364	146	124
2.8	2.0	2806	2058	1981	364	146	124
3.5	2.0	3506	2058	1981	364	146	124
4.2	2.0	4206	2058	1981	364	146	124
4.9	2.0	4906	2058	1981	364	146	124
5.6	2.0	5606	2058	1981	364	146	124
6.3	2.0	6306	2058	1981	364	146	124
7.0	2.0	7006	2058	1981	364	146	124
7.7	2.0	7706	2058	1981	364	146	124
8.4	2.0	8406	2058	1981	364	146	124
9.1	2.0	9106	2058	1981	364	146	124
9.8	2.0	9806	2058	1981	364	146	124
10.5	2.0	10506	2058	1981	364	146	124
2.1	2.5	2106	2548	2471	461	146	124
2.8	2.5	2806	2548	2471	461	146	124
3.5	2.5	3506	2548	2471	461	146	124
4.2	2.5	4206	2548	2471	461	146	124
4.9	2.5	4906	2548	2471	461	146	124
5.6	2.5	5606	2548	2471	461	146	124
6.3	2.5	6306	2548	2471	461	146	124
7.0	2.5	7006	2548	2471	461	146	124
7.7	2.5	7706	2548	2471	461	146	124
8.4	2.5	8406	2548	2471	461	146	124
9.1	2.5	9106	2548	2471	461	146	124
9.8	2.5	9806	2548	2471	461	146	124
10.5	2.5	10506	2548	2471	461	146	124
2.1	3.0	2106	3038	2961	545	146	124
2.8	3.0	2806	3038	2961	545	146	124
3.5	3.0	3506	3038	2961	545	146	124
4.2	3.0	4206	3038	2961	545	146	124
4.9	3.0	4906	3038	2961	545	146	124
5.6	3.0	5606	3038	2961	545	146	124
6.3	3.0	6306	3038	2961	545	146	124
7.0	3.0	7006	3038	2961	545	146	124
7.7	3.0	7706	3038	2961	545	146	124
8.4	3.0	8406	3038	2961	545	146	124
9.1	3.0	9106	3038	2961	545	146	124
9.8	3.0	9806	3038	2961	545	146	124
10.5	3.0	10506	3038	2961	545	146	124
2.1	3.5	2106	3538	3461	624	146	124
2.8	3.5	2806	3538	3461	624	146	124
3.5	3.5	3506	3538	3461	624	146	124
4.2	3.5	4206	3538	3461	624	146	124
4.9	3.5	4906	3538	3461	624	146	124
5.6	3.5	5606	3538	3461	624	146	124
6.3	3.5	6306	3538	3461	624	146	124
7.0	3.5	7006	3538	3461	624	146	124
7.7	3.5	7706	3538	3461	624	146	124
8.4	3.5	8406	3538	3461	624	146	124
9.1	3.5	9106	3538	3461	624	146	124
9.8	3.5	9806	3538	3461	624	146	124
10.5	3.5	10506	3538	3461	624	146	124
3.1	4.0	3106	4028	3951	711	146	124
4.2	4.0	4206	4028	3951	711	146	124
5.2	4.0	5206	4028	3951	711	146	124
6.3	4.0	6306	4028	3951	711	146	124
7.4	4.0	7406	4028	3951	711	146	124
8.4	4.0	8406	4028	3951	711	146	124
9.0	4.0	9006	4028	3951	711	146	124
9.4	4.0	9406	4028	3951	711	146	124
10.0	4.0	10006	4028	3951	711	146	124

Document: Omega Glass Clear Canopy, Major Canopy Dimensions
 Description: Omega Glass Clear Canopy, Lean-To style, post-supported,
 Glass Clear Plate Polycarbonate Roof Panels

Key Canopy Dimensions for Roof Pitch 15 degrees

Width (m)	Projection (m)	Actual width (mm)	Actual Projection (mm) to outside edge of eaves beam (roof pitch 15 degrees)	Projection wall to inside face of supporting post (mm) Roof Pitch = 15 degrees	Dimension from bottom of wall plate to bottom of eaves beam (mm) Roof pitch = 15 degrees	Vertical dimension from top of Wall plate to bottom of wall plate (mm)	Vertical dimension of face of wall plate immediately adjacent wall (mm)
2.1	1.5	2106	1538	1460	400	146	124
2.8	1.5	2806	1538	1460	400	146	124
3.5	1.5	3506	1538	1460	400	146	124
4.2	1.5	4206	1538	1460	400	146	124
4.9	1.5	4906	1538	1460	400	146	124
5.6	1.5	5606	1538	1460	400	146	124
6.3	1.5	6306	1538	1460	400	146	124
7.0	1.5	7006	1538	1460	400	146	124
7.7	1.5	7706	1538	1460	400	146	124
8.4	1.5	8406	1538	1460	400	146	124
9.1	1.5	9106	1538	1460	400	146	124
9.8	1.5	9806	1538	1460	400	146	124
10.5	1.5	10506	1538	1460	400	146	124
2.1	2.0	2106	2018	1940	529	146	124
2.8	2.0	2806	2018	1940	529	146	124
3.5	2.0	3506	2018	1940	529	146	124
4.2	2.0	4206	2018	1940	529	146	124
4.9	2.0	4906	2018	1940	529	146	124
5.6	2.0	5606	2018	1940	529	146	124
6.3	2.0	6306	2018	1940	529	146	124
7.0	2.0	7006	2018	1940	529	146	124
7.7	2.0	7706	2018	1940	529	146	124
8.4	2.0	8406	2018	1940	529	146	124
9.1	2.0	9106	2018	1940	529	146	124
9.8	2.0	9806	2018	1940	529	146	124
10.5	2.0	10506	2018	1940	529	146	124
2.1	2.5	2106	2498	2420	659	146	124
2.8	2.5	2806	2498	2420	659	146	124
3.5	2.5	3506	2498	2420	659	146	124
4.2	2.5	4206	2498	2420	659	146	124
4.9	2.5	4906	2498	2420	659	146	124
5.6	2.5	5606	2498	2420	659	146	124
6.3	2.5	6306	2498	2420	659	146	124
7.0	2.5	7006	2498	2420	659	146	124
7.7	2.5	7706	2498	2420	659	146	124
8.4	2.5	8406	2498	2420	659	146	124
9.1	2.5	9106	2498	2420	659	146	124
9.8	2.5	9806	2498	2420	659	146	124
10.5	2.5	10506	2498	2420	659	146	124
2.1	3.0	2106	2988	2910	788	146	124
2.8	3.0	2806	2988	2910	788	146	124
3.5	3.0	3506	2988	2910	788	146	124
4.2	3.0	4206	2988	2910	788	146	124
4.9	3.0	4906	2988	2910	788	146	124
5.6	3.0	5606	2988	2910	788	146	124
6.3	3.0	6306	2988	2910	788	146	124
7.0	3.0	7006	2988	2910	788	146	124
7.7	3.0	7706	2988	2910	788	146	124
8.4	3.0	8406	2988	2910	788	146	124
9.1	3.0	9106	2988	2910	788	146	124
9.8	3.0	9806	2988	2910	788	146	124
10.5	3.0	10506	2988	2910	788	146	124
2.1	3.5	2106	3468	3390	917	146	124
2.8	3.5	2806	3468	3390	917	146	124
3.5	3.5	3506	3468	3390	917	146	124
4.2	3.5	4206	3468	3390	917	146	124
4.9	3.5	4906	3468	3390	917	146	124
5.6	3.5	5606	3468	3390	917	146	124
6.3	3.5	6306	3468	3390	917	146	124
7.0	3.5	7006	3468	3390	917	146	124
7.7	3.5	7706	3468	3390	917	146	124
8.4	3.5	8406	3468	3390	917	146	124
9.1	3.5	9106	3468	3390	917	146	124
9.8	3.5	9806	3468	3390	917	146	124
10.5	3.5	10506	3468	3390	917	146	124
3.1	4.0	3106	3948	3870	1047	146	124
4.2	4.0	4206	3948	3870	1047	146	124
5.2	4.0	5206	3948	3870	1047	146	124
6.3	4.0	6306	3948	3870	1047	146	124
7.4	4.0	7406	3948	3870	1047	146	124
8.4	4.0	8406	3948	3870	1047	146	124
9.0	4.0	9006	3948	3870	1047	146	124
9.4	4.0	9406	3948	3870	1047	146	124
10.0	4.0	10006	3948	3870	1047	146	124

Document: Omega Glass Clear Canopy, Major Canopy Dimensions
 Description: Omega Glass Clear Canopy, Lean-To style, post-supported,
 Glass Clear Plate Polycarbonate Roof Panels

Page 4 of 4

Key Canopy Dimensions for Roof Pitch 20 degrees

Width (m)	Projection (m)	Actual width (mm)	Actual Projection (mm) to outside edge of eaves beam (roof pitch 20 degrees)	Projection wall to inside face of supporting post (mm) Roof Pitch = 20 degrees	Dimension from bottom of wall plate to bottom of eaves beam (mm) Roof pitch = 20 degrees	Vertical dimension from top of Wall plate to bottom of wall plate (mm)	Vertical dimension of face of wall plate immediately adjacent wall (mm)
2.1	1.5	2106	1488	1420	520	146	124
2.8	1.5	2806	1488	1420	520	146	124
3.5	1.5	3506	1488	1420	520	146	124
4.2	1.5	4206	1488	1420	520	146	124
4.9	1.5	4906	1488	1420	520	146	124
5.6	1.5	5606	1488	1420	520	146	124
6.3	1.5	6306	1488	1420	520	146	124
7.0	1.5	7006	1488	1420	520	146	124
7.7	1.5	7706	1488	1420	520	146	124
8.4	1.5	8406	1488	1420	520	146	124
9.1	1.5	9106	1488	1420	520	146	124
9.8	1.5	9806	1488	1420	520	146	124
10.5	1.5	10506	1488	1420	520	146	124
2.1	2.0	2106	1968	1890	691	146	124
2.8	2.0	2806	1968	1890	691	146	124
3.5	2.0	3506	1968	1890	691	146	124
4.2	2.0	4206	1968	1890	691	146	124
4.9	2.0	4906	1968	1890	691	146	124
5.6	2.0	5606	1968	1890	691	146	124
6.3	2.0	6306	1968	1890	691	146	124
7.0	2.0	7006	1968	1890	691	146	124
7.7	1.5	7706	1968	1890	691	146	124
8.4	1.5	8406	1968	1890	691	146	124
9.1	1.5	9106	1968	1890	691	146	124
9.8	1.5	9806	1968	1890	691	146	124
10.5	1.5	10506	1968	1890	691	146	124
2.1	2.5	2106	2488	2360	862	146	124
2.8	2.5	2806	2488	2360	862	146	124
3.5	2.5	3506	2488	2360	862	146	124
4.2	2.5	4206	2488	2360	862	146	124
4.9	2.5	4906	2488	2360	862	146	124
5.6	2.5	5606	2488	2360	862	146	124
6.3	2.5	6306	2488	2360	862	146	124
7.0	2.5	7006	2488	2360	862	146	124
7.7	1.5	7706	2488	2360	862	146	124
8.4	1.5	8406	2488	2360	862	146	124
9.1	1.5	9106	2488	2360	862	146	124
9.8	1.5	9806	2488	2360	862	146	124
10.5	1.5	10506	2488	2360	862	146	124
2.1	3.0	2106	2908	2830	1037	146	124
2.8	3.0	2806	2908	2830	1037	146	124
3.5	3.0	3506	2908	2830	1037	146	124
4.2	3.0	4206	2908	2830	1037	146	124
4.9	3.0	4906	2908	2830	1037	146	124
5.6	3.0	5606	2908	2830	1037	146	124
6.3	3.0	6306	2908	2830	1037	146	124
7.0	3.0	7006	2908	2830	1037	146	124
7.7	3.0	7706	2908	2830	1037	146	124
8.4	3.0	8406	2908	2830	1037	146	124
9.1	3.0	9106	2908	2830	1037	146	124
9.8	3.0	9806	2908	2830	1037	146	124
10.5	3.0	10506	2908	2830	1037	146	124
2.1	3.5	2106	3378	3300	1207	146	124
2.8	3.5	2806	3378	3300	1207	146	124
3.5	3.5	3506	3378	3300	1207	146	124
4.2	3.5	4206	3378	3300	1207	146	124
4.9	3.5	4906	3378	3300	1207	146	124
5.6	3.5	5606	3378	3300	1207	146	124
6.3	3.5	6306	3378	3300	1207	146	124
7.0	3.5	7006	3378	3300	1207	146	124
7.7	3.5	7706	3378	3300	1207	146	124
8.4	3.5	8406	3378	3300	1207	146	124
9.1	3.5	9106	3378	3300	1207	146	124
9.8	3.5	9806	3378	3300	1207	146	124
10.5	3.5	10506	3378	3300	1207	146	124
3.1	4.0	3106	3848	3770	1377	146	124
4.2	4.0	4206	3848	3770	1377	146	124
5.2	4.0	5206	3848	3770	1377	146	124
6.3	4.0	6306	3848	3770	1377	146	124
7.4	4.0	7406	3848	3770	1377	146	124
8.4	4.0	8406	3848	3770	1377	146	124
9.0	4.0	9006	3848	3770	1377	146	124
9.4	4.0	9406	3848	3770	1377	146	124
10.0	4.0	10006	3848	3770	1377	146	124